

SIEMENS

Ingenuity for life

HIT Portal

Malleable cast iron fitting G 2³/₄" / Rp 2", set of 3

Stock No.: BPZ:ALG503

Cylindric thread to ISO 228-1 on the valve side.
Tapered R-externally or cylindrical Rp-internally
threaded to ISO 7-1 on the pipe side.
Each fitting set ALG..3 consists of 3 cap nuts, 3
insert nuts and 3 flat seals.

Additional info

Pipe side internally threaded.

Technical Specifications

Connecting thread, pipe side:	Rp 2 "
Connecting thread, valve side:	G 2 ³ / ₄ "
DN:	50
Material:	Phosphated malleable cast iron



Ordering Information: Part No. SBALG503

T: 09 636 1401 | E: sales@systemcontrol.co.nz | W: systemcontrol.co.nz

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

SCE
SYSTEM CONTROL
ENGINEERING